

a supply of fluid located within said smoke producing chamber to be vaporized when heated;

a heating element located within said smoke producing chamber above said supply of fluid;

a gas inlet communicating with said smoke producing chamber to receive non-combustible nitrogen gas under pressure, said gas inlet having an inlet orifice in fluid communication with said supply of fluid so that when said nitrogen gas under pressure is delivered through said gas inlet, some of said supply of fluid is drawn into said gas inlet via said inlet orifice, whereby a mixture of said nitrogen gas and fluid is blown through said gas inlet and against said heating element to be vaporized into smoke when said heating element is heated;

a smoke outlet communicating with said smoke producing chamber to permit said smoke to exit said smoke producing chamber; and

a source of non-combustible nitrogen gas connected to said gas inlet to supply said nitrogen gas under pressure thereto.

3. The apparatus recited in claim 1, wherein said gas inlet is a tube located within said smoke producing chamber, said gas inlet tube running through and extending above said supply of fluid to blow the mixture of nitrogen gas and fluid against said heating element.

19. (Amended) A method for generating smoke, comprising the steps of:

locating a supply of fluid within a closed smoke producing chamber, said smoke producing chamber having a gas inlet to receive a supply of non-combustible nitrogen gas under pressure and a smoke outlet to permit smoke to exit said smoke producing chamber;

~~B2~~
~~Entd~~
Sub
Cand.

~~B2~~
~~Entd~~
Sub
Cand.

~~B2~~
~~Entd~~
Sub
Cand.

~~B2~~
~~Entd~~
Sub
Cand.

B²

PA